

## NORTHSTAR RANGE FEATURES AND SPECIFICATIONS

| SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE   | 1947<br>DUAL FUEL | 1954<br>ALL-ELECTRIC | 1955<br>DUAL FUEL    | 1956<br>ALL-GAS     |
|---|-------------------|----------------------|----------------------|---------------------|
| <b>DIMENSIONS:</b>  |                   |                      |                      |                     |
| Width   | 36"               | 30"                  | 30"                  | 30"                 |
| Height  | 49"               | 49"                  | 49"                  | 49"                 |
| Height to Cooking Surface   | 37-1/4"           | 36"                  | 38"                  | 38"                 |
| Depth (plus 2" handles)   | 28-1/2"           | 28-1/2"              | 28-1/2"              | 28-1/2"             |
| <b>OVEN:</b>  |                   |                      |                      |                     |
| Fuel  | Electric          | Electric             | Electric             | Gas – LP or Natural |
| Capacity (Cubic Feet)   | 5.0               | 4.3 (4.0 Convection) | 4.3 (4.0 Convection) | 4.0                 |
| Width   | 31"               | 25"                  | 25"                  | 25"                 |
| Height  | 15-1/2"           | 16"                  | 16"                  | 15-1/2"             |
| Depth (Standard / Convection)   | - / 18"           | 17-1/2" / 16-1/2"    | 17-1/2" / 16-1/2"    | - / 17-1/2"         |
| Delayed Start Baking / Cleaning   | ●                 | ●                    | ●                    | ●                   |
| Variable Temperature Broil  | ●                 | ●                    | ●                    | ●                   |
| Door-Activated Light with Override  | Halogen           | Halogen              | Halogen              | Incandescent        |
| Commercial-Grade Plated Racks   | ●                 | ●                    | ●                    | ●                   |
| True Convection   | Standard          | Optional             | Optional             | Not Available       |
| <b>RANGE TOP:</b>   |                   |                      |                      |                     |
| Electric High-Speed Radiant Elements  |                   | ●                    |                      |                     |
| 1,500 Watt Radiant (Rear)   |                   | 2                    |                      |                     |
| 2,000 Watt Radiant (Front Left)   |                   | 1                    |                      |                     |
| 2,500 Watt Radiant (Front Right)  |                   | 1                    |                      |                     |
| Gas Sealed Burners with Cast Grates   | ●                 |                      | ●                    | ●                   |
| 8,000* BTU Gas Burners (Rear)   | 3                 |                      | 2                    | 2                   |
| 15,000* BTU Gas Burner (Front Left)   | 1                 |                      | 1                    | 1                   |
| 15,000* BTU Gas Burner (Front Right)  | 1                 |                      |                      |                     |
| 12,000* BTU Gas Burners (Front Right)   |                   |                      | 1                    | 1                   |
| 12,000* BTU Gas Burner (Front Center)   | 1                 |                      |                      |                     |
| Electronic Spark with Re-Ignition   | ●                 |                      | ●                    | ●                   |
| * Ratings are for Natural Gas; Liquid Propane is approximately 10% lower  |                   |                      |                      |                     |
| Power Rating - Natural Gas (BTUs)   | 66,000            |                      | 43,000               | 58,000              |
| Power Rating – Liquid Propane (BTUs)  | 59,400            |                      | 38,700               | 52,000              |
| Power Rating – Oven Burner NG (BTUs)  |                   |                      |                      | 16,000              |
| Power Rating – Oven Burner LP (BTUs)  |                   |                      |                      | 14,400              |
| Electrical Power Source (208 – 250V)  | 220V – 40A        | 220V – 40A           | 220V – 25A           | 110V – 10A          |
| <b>STAINLESS STEEL WARMER DRAWER (BECOMES STORAGE WHEN NOT IN USE):</b>   |                   |                      |                      |                     |
| Located in Lower Drawer   | Not Available     | Optional             | Optional             | Not Available       |
| Dimensions 26-3/4"W x 22-1/2"D x 5-3/8" H   |                   |                      |                      |                     |
| <b>SHIPPING WEIGHT (LB.):</b>   | 375               | 305                  | 315                  | 325                 |
| All 220V ranges come with a standard four-wire range cord attached. NOTE: The January 1998 electrical standard requires that a four-wire range cord be used in all new construction. Please advise us if a three-wire range cord is required (used only in existing construction). Electrical receptacle and gas piping should be installed approximately in the center of the opening, 6 inches above the floor. |                   |                      |                      |                     |